

# TECHNICAL SPECIFICATION



## Replacement Integrated Shield for EVO® VISTAshield®

Replacement Integrated Shield for EVO® VISTAshield™ / AMV200-000-000



### DESCRIPTION

Replacement Integrated Anti Mist Anti Scratch KN Shield for EVO®VISTAshield® Helmet

When fitted to the EVO®VISTAshield® Helmet this replacement shield has the following features and benefits -

Optical Class 1 - High optical quality with no optical distortion

K Rated - Anti-Scratch resistance to surface damage from fine particles

N Rated - Anti-Mist resistance to fogging

A - Impact Rating. High energy impact; 6mm, 0.86g ball travelling at 425mph (685kph)

UV 2C-1.2 2: UV filter (EN170) provides protection from harmful UV. C: Unimpaired colour perception. 1.2: High light transmission.

### OPTIONS

**Replacement Integrated Shield for EVO® VISTAshield™ (AMV200-000-000)**

### SAFETY STANDARDS

EN 166 • EN 170

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jpsafety.com / Web: www.jpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 31 Jan 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



## SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect  
Scale Number  
2C



LIGHT TRANSMISSION BREAKDOWN Lens Shade number  
1.2



Manufacturer's Trademark  
**JSP Dagger**



High Energy Impact resists a 6 mm, 0.86g ball @ 190 m/s  
Maximum protection for face shields



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)  
1



Resistance to Surface Damage by Fine Particles (optional)  
K



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional  
T



Visor Length  
12.5cm



Resistance to fogging (optional)  
N



Recyclable  
Yes



Material  
**Polycarbonate**



BSI Kitemark  
Yes



Product Weight  
103g

## VIDEOS

▶ [www.youtube.com/watch?v=i8-pUrIrl1o](https://www.youtube.com/watch?v=i8-pUrIrl1o)

## DOWNLOADS

Image Pack (ZIP)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jpsafety.com](mailto:sales@jpsafety.com) / Web: [www.jpsafety.com](http://www.jpsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jpsafety.com](mailto:copyright@jpsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 31 Jan 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

