TECHNICAL SPECIFICATION



Replacement Integrated Shield for EVO® VISTAshield®

Replacement Integrated Shield for EVO® VISTAshield™ / AMV200-000-000



DESCRIPTION

Replacement Integrated Anti Mist Anti Scratch KN Shield for EVO®VISTAshield® Helmet

When fitted to the EVO®VISTAshield® Helmet this replacement shield has the following features and benefits -

Optical Class 1 - High optical quality with no optical distortion

K Rated - Anti-Scratch resistance to surface damage from fine particles N Rated - Anti-Mist resistance to fogging

A - Impact Rating. High energy impact; 6mm, 0.86g ball travelling at 425mph (685kph)

UV 2C-1.2 2: UV filter (EN170) provides protection from harmful UV. C: Unimpaired colour perception. 1.2: High light transmission.

OPTIONS

Replacement Integrated Shield for EVO® VISTAshield™ (AMV200-000-000)

SAFETY STANDARDS

EN 166 • EN 170





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com







SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect Scale Number

2C



Manufacturer's Trademark

JSP Dagger



High Energy Impact resists a 6 mm, 0.86g ball @ 190 m/s Maximum protection for face shields



Resistance to Surface Damage by Fine Particles (optional)



Visor Length 12.5cm



Recyclable

Yes



BSI Kitemark

Yes



LIGHT TRANSMISSION BREAKDOWN Lens Shade number 1.2



Optical Class (1 - Class 1 - High quality for regular use. 2 -Class 2 - Medium quality for occasional use. 3 - Class 3 -Low quality for exceptional use)



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional

Т



Resistance to fogging (optional)

Ν

Material

Polycarbonate



Product Weight

103g

VIDEOS

www.youtube.com/watch?v=i8-pUrIrl1o





Image Pack (ZIP)









