TECHNISCHE SPEZIFIKATION



EVO® ALTA™ Skyworker™

Black / ARC170-001-100



BESCHREIBUNG

The new EVO® ALTA™ offers all-round impact protection. The mountaineering-style helmet features a specialised shell structure and internal liner to increase durability and shock absorption performance. Precise adjustment settings enable a secure fit, ensuring the helmet remains stable. Engineered to maximise compatibility and accessory integration, EVO® ALTA™ is an adaptive system with built-in attachment points and an interchangeable front module.

EVO® ALTA™ Skyworker™ is certified to the EN 12492 mountaineering helmet standard with a 4-point chinstrap designed to stay secure under force, maximising security during a fall.

OPTIONEN

Black (ARC170-001-100)

Blue (ARC170-000-500)

Extra-Visibility Orange (ARC170-001-600)

Extra Visibility Red (ARC170-000-600)

Extra Visibility Yellow (ARC170-00C-700)

Green (ARC170-000-300)

Grey (ARC170-000-400)

White (ARC170-000-100)

SICHERHEITSSTANDARDS

EN 12492





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com







SPEZIFIKATIONEN



Schirm Mikro



Seitliche Schlagfestigkeit



25 Joules



Seitliche Verformung

Meets performance requirements



Max. Temperatur +50°C



ABS-Schale





Wiederverwendbar





Belüftung Ja



Drehradverschluss



Universeller Zubehör-Steckplatz

Ja



ID-Ausweishalter

Optional



Produktgewicht

500g



Stoßfestigkeit 100 Joules



Schmelzmetall

Meets performance requirements



EN 50365 ELEKTRISCHE ISOLIERUNG Meets performance requirements



Min. Temperatur

-40°C



EPP-Aufprall Absorber

Ja



Textil

Innenausstattung



Tiefeneinstellung

3D-Anpassung



Ausgestattet mit 4-Punkt-Kinnriemen (entspricht: EN 12492)

Ausgestattet



Reflektierendes CR2

Optional



JSPCheck

Ja



Größe

53-64cm

EIGENSCHAFTEN



All-Round Protection

EVO® ALTA™ provides all-round impact protection with top, side, front and rear shock absorption performance. The helmet is designed with an extended nape section to offer greater neck coverage.



Compatibility & Accessories

The EVO® Alta™ range maximises compatibility and accessory integration. Attachment points on the helmet shell enable firm fitting of ear defenders, faceshields, goggle and lamp straps, plus a range of other accessories.



Maximum Comfort

The Revolution® Flex wheel ratchet harness secures the helmet, eliminating pressure points to provide maximum comfort. Fitted with a replaceable Chamlon™ cotton sweatband and fully compatible with EVO® cooling sweatbands for protection against heat stress.



Interchangeable Front Module

EVO® ALTA™ features a unique interchangeable front module. Select the integrated ID card holder for on-site identification or choose the logo-ready standard front to apply company branding. Both front modules enable attachment of a helmet lamp and other accessories.



EPP Liner

EVO® ALTA™ features an internal impact liner to increase shock absorption and penetration protection. Manufactured in expanded polypropylene (EPP), the liner is lightweight and ventilated for comfort.



Secure Fit


The harness cradles the head to keep the helmet stable with an adjustable 4-point chinstrap for increased security. 3D-Adjustment depth settings enable the most precise fit attainable on a safety helmet.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com









4-Point Chinstrap

The 4-point chinstrap is easy to adjust on the head. Size and anchorage point adjustment enable a tailored fit for different head sizes, ensuring stability and greater comfort.



Custom Branding

Helmets can be customised to meet a corporate identity. Logo printing is available for the standard front module, helping to increase brand recognition and discourage theft. MOQs apply.



Dual Ventilation

Side and rear ventilation in the helmet's shell and liner reduce temperatures by an average 2-3 degrees.

LOGO

✓ Vorderseite



SERIE



DOWNLOADS

Bilderordner (ZIP)













