TECHNICAL SPECIFICATION



SpringFit[™] Disposable Dust Mask 421ML FFP2

Box of 10 / BGA122-202-000



DESCRIPTION

The SpringFit[™] fold flat disposable mask achieves an unrivalled secure fit with the use of a unique endoskeleton structure. SpringFit[™] introduces an abundance of features that maximise fit, comfort, compatibility and performance.

OPTIONS

Box of 10 (BGA122-202-000)

SAFETY STANDARDS

EN 149 • EN 14683















SPECIFICATIONS

Classification

FFP2 (Filtering Facepiece Particulate)

Usage

NR (Non-Reusable)



Activated Carbon Layer

No

Maximum Total Inward Leakage (TIL)

8%

UK Assigned Protection Factor

10



Exhalation Valve

None



Nose Bridge

Encapsulated Adjustable Wire

Metal Free

No

Filter Shelf Life

5 Years



Product Weight

13g



Filter Type

P (Protects Against Solid and Liquid Aerosols)



(D) Resistance to dust clogging

Yes - D marking = passes optional clogging test

Minimum Filtration Efficiency 94% For FFP2 Rated

Nominal Protection Factor

12

Mask Design Fold Flat

2 Point Harness adjustment system

Yes

Latex free

Yes

Mask Material Polypropylene



BSI Kitemark

Yes

FEATURES



Endoskeleton Structure

The internal skeleton frame guarantees that each mask keeps its shape, increasing performance and maintaining rigidity. The integrated spring feature absorbs facial movements ensuring a secure face fit and seal.



Compatibility and Vision

The low profile design of the SpringFit™ provides exceptional compatibility with other above the neck PPE, such as eyewear. The low profile also offers an improved field of vision for the wearer.



Compact

The fold flat design makes SpringFit™ more compact, and easily pocketed. SpringFit™ is also individually packed to ensure a high level of hygiene.



Comfort

The welded nose piece gives a tighter fit and minimises irritation. The adjustable strap means that SpringFit™ can be fitted comfortably to all head sizes and shapes. A foam area around the inside of the mask provides a comfortable fit.

RANGE VIDEOS



youtu.be/uqObtEODVSY

youtu.be/GMp8O9xw1t8

DOWNLOADS



doc-springfit-400-series-421.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



