TECHNICAL SPECIFICATION

EVOGuard® C2 Industrial Browguard System

EVOGuard® C2 Industrial Browguard System / ADB28A-100-400



DESCRIPTION

EVOGuard® C2 Industrial Browguard System provides comprehensive facial coverage without limiting movement. The optical class 1 visor offers UV protection and a panoramic view with minimal distortion.

The system provides BT rated impact, liquid splash, and molten metal protection, and is also fitted with Sonis®C ear defenders offering an SNR of 31dB.

OPTIONS

EVOGuard® C2 Industrial Browguard System (ADB28A-100-400)

SAFETY STANDARDS

EN 170 • EN 352-3 • EN 166

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Harness
NEW Rake. 6 positions. sizing strap over head. Extra long sweat band.

Wheel Ratchet
Yes NEW Sprung comfort pad

RADIATION PROTECTION BREAKDOWN filtering effect Scale Number
2C

Manufacturer's Trademark
JSP Dagger

Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.
B - When Fitted To EVOGuard® Browguard

Protection from Liquid Splash
3

Resistance to Surface Damage by Fine Particles (optional)
K

Visor Length
18.5cm

SNR
31 dB

Hygiene
Hygiene Kits

JSPCheck
Yes

Material
Polycarbonate Shield

Recyclable
Yes

Lens Thickness - centre
2.00mm

Universal Accessories Slot
Yes

Integrated Eyewear
Fitted

LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.2

Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1

The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5˚C and +55˚C) Optional
T

Resistance to Molten Metals and Hot Solids (optional)
9

Resistance to fogging (optional)
N

Mounting
Browguard/Helmet

Adjustable
Yes

BSI Kitemark
Yes

Material
30% Glass Filled Nylon Browguard

Material
ABS/Stainless Steel Wire

Product Weight
655g


Lens Thickness - edge
1.70mm

FEATURES



Compatibility

EVOGuard® visors maximise compatibility with JSP half masks, disposable respirators, prescription glasses and the Sonis® helmet mounted ear defender range.



Vision

The optical class 1 visor offers a panoramic view with minimal distortion, ideal for comfortable all day wear.



Impact

Wide range of high performance visors offering up to A rated impact resistance when fitted to a safety helmet and medium energy impact protection with the EVOGuard® browguard.



Coverage

EVOGuard® visors provide comprehensive facial coverage without limiting movement. EVOGuard® MAX visors offer enhanced coverage with an integral chinguard.

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.




Eye and Face Protection

The full EVOGuard®C Industrial eye protection range is made with optical class 1 material. They provide UV protection and can provide the same level of protection even at extreme temperatures.



Compatibility

EVOGuard® visors maximise compatibility with JSP half masks, disposable respirators, prescription glasses and the Sonis® helmet mounted ear defender range. Also can be worn over a Hardcap® Aerolite™



Performance

Cup size and weight, along with frequency optimised foam sections, ensure performance is guaranteed, no matter what your hearing protection requirements are.



Adjustable Steel Arms

The wearer can tilt and adjust the position of the cup for optimum comfort and fit, also offering even distribution of pressure.



Supreme Comfort

Features the new JSP Revolution® wheel ratchet, securely tightening and holding the unit firmly in position, no matter the task or amount of user movement involved.



Maximum Adjustability

Multiple fitting positions allow the wearer to adjust the browguard in three ways. An over the crown slide fitting combined with a forward and back adjustment, maximises compatibility with different head shapes.



Comfort

The force the helmet adaptor applies and the cushion surface area work together to provide optimum cushion pressure and comfort.



Universal Compatibility

The universal slots of JSP helmets and browguard systems allow for the easy fitting of the Sonis® ear defenders.

RANGE

EVOGUARD C
INDUSTRIAL RANGE

DOWNLOADS

Image Pack (ZIP)
doc-evoguard.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.