

TECHNISCHE SPEZIFIKATION



15m automatischer Seileinzug

15m automatischer Seileinzug / FAR0707



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 30 Jun 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.





BESCHREIBUNG

Selbstaufrollende Rettungsleine aus 15 m Draht in einem robusten und langlebigen Kunststoffgehäuse, ausgestattet mit einem drehbaren Karabinerhaken aus Stahl und einem Aluminiumverbinder mit Schraubverschluss am Verankerungspunkt. Dieses Produkt verfügt

OPTIONEN

15m automatischer Seileinzug (FAR0707)

SICHERHEITSSTANDARDS

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 30 Jun 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



außerdem über einen Griff zum bequemen Tragen.



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 30 Jun 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



SPEZIFIKATIONEN

Sturzindikator

Ja

Länge

15m

Material

Verzinkter Stahldraht mit einem Durchmesser von 4,5 mm

Falldämpfer

Intern

Scharfkantig

Nein

Gehäuse

Robuster und langlebiger Kunststoff

Bewertete Nennlast

140kg

Produktgewicht

6500g

Tiefeneinstellung

1 drehbarer Stahlkarabinerhaken. Karabineröffnung 20mm. Entspricht EN362 Klasse T. 1 Aluminium-Schraubkarabiner am Verankerungspunkt. Karabineröffnung 22mm. Entspricht EN362 Klasse B

ANWENDUNGEN

Nur allgemeine Hinweise und sollte nicht als Ersatz für eine vollständige Risikobeurteilung angesehen werden

Luffahrt

DOWNLOADS

 [Bilderordner \(ZIP\)](#)

 [doc-far0707-far0712.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 30 Jun 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

