

TECHNISCHE SPEZIFIKATION



15m automatischer Seileinzug

15m automatischer Seileinzug / FAR0707



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 18 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





BESCHREIBUNG

Selbstaufrollende Rettungsleine aus 15 m Drahtseil in einem robusten und langlebigen Kunststoffgehäuse, ausgestattet mit einem drehbaren Karabinerhaken aus Stahl und einem Aluminiumverbinder mit Schraubverschluss am Verankerungspunkt. Dieses Produkt verfügt

OPTIONEN

15m automatischer Seileinzug (FAR0707)

SICHERHEITSSTANDARDS

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 18 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



außerdem über einen Griff zum bequemen Tragen.



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 18 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPEZIFIKATIONEN

Sturzindikator
Ja

Länge
15m

Material
Verzinkter Stahldraht mit einem Durchmesser von
4,5 mm

Falldämpfer
Intern

Scharfkantig
Nein

Gehäuse
Robuster und langlebiger Kunststoff



Bewertete Nennlast
140kg



Produktgewicht
6500g



Tiefeneinstellung
1 drehbarer Stahlkarabinerhaken. Karabineröffnung
20mm. Entspricht EN362 Klasse T. 1 Aluminium-
Schraubkarabiner am Verankerungspunkt.
Karabineröffnung 22mm. Entspricht EN362 Klasse
B

DOWNLOADS

 [Bilderordner \(ZIP\)](#)

 [doc-far0707-far0712.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 18 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

