

# ESPECIFICACIONES TÉCNICAS



## Línea de vida auto-retráctil de acero 15m

Línea de vida auto-retráctil de acero 15m / FAR0707



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





## DESCRIPCIÓN

Línea de vida auto-retráctil de acero 15 m en carcasa de plástico robusta y duradera, equipada con conector de gancho giratorio de acero y conector de aluminio de puerta de tornillo en el punto de anclaje. Este producto también cuenta con una asa para facilidad de

## OPCIONES

**Línea de vida auto-retráctil de acero 15m (FAR0707)**

## NORMAS DE SEGURIDAD

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



## ESPECIFICACIONES

Indicador de caída  
Sí

Longitud  
15m

Material  
Alambre de acero galvanizado de 4,5 mm de diámetro

Absorbedor  
Interno

Borde afilado

Carcasa  
Plástico robusto y duradero



Peso/carga nominal  
140kg



Peso del producto  
6500g



Ajuste de profundidad  
1 Mosquetón giratorio de acero. Abertura 20mm.  
Cumple con EN362 Clase T. 1 Conector de aluminio de puerta de tornillo en el punto de anclaje. Abertura 22mm. Conforme a EN362 Clase B

## DESCARGAR

[Colección de imágenes \(ZIP\)](#)

[doc-far0707-far0712.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

