

Enrouleur à rappel automatique câble 15m

Enrouleur à rappel automatique câble 15m / FAR0707



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 24 Apr 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.





DESCRIPTION

Ligne de vie auto-rétractable de fil de 15 m dans un boîtier en plastique robuste et durable, équipé d'un connecteur à mousqueton pivotant en acier et d'un connecteur en aluminium à vis au point d'ancrage. Ce produit dispose également d'une poignée pour un transport pratique.

OPTIONS

Enrouleur à rappel automatique câble 15m (FAR0707)

NORMES

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 24 Apr 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 24 Apr 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



INFORMATIONS TECHNIQUES

Indicateur de chute
Oui

Matériau
Câble en acier galvanisé diamètre 45mm

Arrêtes vives
Non



Poids/charge nominal
140kg

Longueur
15m

Absorbeur d'énergie
Interne

Boîtier
Plastique robuste et durable



Poids du produit
6500g



Ajustement de la profondeur
1 Crochet mousqueton pivotant en acier Ouverture
20mm. Répond à la norme EN 362 classe T. 1
connecteur à vis aluminium au point d'ancrage.
Ouverture 22mm. Conforme à EN362 Classe B

TÉLÉCHARGEMENTS

 [Pack d'images \(ZIP\)](#)

 [doc-far0707-far0712.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 24 Apr 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

