

## Enrouleur à rappel automatique câble 15m

Enrouleur à rappel automatique câble 15m / FAR0707



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jsp-safety.com](mailto:sales@jsp-safety.com) / Web: [www.jsp-safety.com](http://www.jsp-safety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jsp-safety.com](mailto:copyright@jsp-safety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 22 Nov 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.





## DESCRIPTION

Ligne de vie auto-rétractable de fil de 15 m dans un boîtier en plastique robuste et durable, équipé d'un connecteur à mousqueton pivotant en acier et d'un connecteur en aluminium à vis au point d'ancrage. Ce produit dispose également d'une poignée pour un transport pratique.

## OPTIONS

**Enrouleur à rappel automatique câble 15m (FAR0707)**

## NORMES

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 22 Nov 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 22 Nov 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



## INFORMATIONS TECHNIQUES

Indicateur de chute  
Oui

Matériau  
Câble en acier galvanisé diamètre 45mm

Arrêtes vives  
Non

Poids/charge nominal  
140kg

Ajustement de la profondeur  
1 Crochet mousqueton pivotant en acier Ouverture  
20mm. Répond à la norme EN 362 classe T. 1  
connecteur à vis aluminium au point d'ancrage.  
Ouverture 22mm. Conforme à EN362 Classe B

Longueur  
15m

Absorbeur d'énergie  
Interne

Boîtier  
Plastique robuste et durable

Poids du produit  
6500g

## APPLICATIONS

Conseils et recommandations uniquement à caractère indicatif qui ne doivent pas être considérés comme un substitut à une évaluation complète des risques.

Aéronautique

## TÉLÉCHARGEMENTS

 [Pack d'images \(ZIP\)](#)

 [doc-far0707-far0712.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 22 Nov 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

