

15m Draad Zelfoprolbare reddingslijn

15m Draad Zelfoprolbare reddingslijn / FAR0707



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





BESCHRIJVING

15m draad zelfoprolbare leeflijn in robuuste en duurzame kunststof behuizing, uitgerust met stalen draaibare karabijnhaak connector en aluminium schroefpoort connector op verankeringspunt. Dit product heeft ook een handvat om het gemakkelijk te dragen.

OPTIES

15m Draad Zelfoprolbare reddingslijn (FAR0707)

VEILIGHEIDSNORMEN

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPECIFICATIES

Valindicator
Ja

Lengte
15m

Materiaal
Gegalvaniseerde staaldraad 4,5mm diameter

Schokdemper
Intern

Scherpe rand
Nein

Behuizing
Robuust en duurzaam plastic



Nominaal gewicht / belasting
140 kg



Gewicht product
6500g



Diepte-instelling
1 Stalen draaibare karabijnhaak. Poortopening 20 mm. Voldoet aan EN362 Klasse T. 1 Aluminium schroefverbinding bij het verankeringspunt. Poortopening 22 mm. Voldoet aan EN362 Klasse B

DOWNLOADS

 [Pakket afbeeldingen \(ZIP\)](#)

 [doc-far0707-far0712.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

