

# ESPECIFICACIONES TÉCNICAS



## Swiss One LYSS

1LYSDG23SKN / 1LYSDG23SKN



### DESCRIPCIÓN

Discover the new Eyewear generation... Lyss™ eyewear with Swiss One Flexofit technology... Angle adjustable nose pad for exceptional fit and adjustment for any situation... Worker comfort for many facial profiles. Soft cushioning browguard, pantoscopic temples with 3 side inclination positions and a unique up and down inclinable nose bridge concept to fit all nose shapes. THE fully adjustable spectacle!

### OPCIONES

1LYSBB23CKN (1LYSBB23CKN)  
1LYSBY23CKN (1LYSBY23CKN)  
1LYSDG23CKN (1LYSDG23CKN)  
**1LYSDG23SKN (1LYSDG23SKN)**

### NORMAS DE SEGURIDAD

EN 172 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.






Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com





Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 6 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



## ESPECIFICACIONES

	<b>PROTECCIÓN RADIOLÓGICA</b> Valor de escala de efecto de filtrado 5
	Marca del fabricante Swiss One <b>Swiss One</b>
	El impacto de baja energía resiste una bola de 6 mm, 0,86 g a 45 m/s de Máxima protección para gafas <b>F</b>
	Resistencia al daño superficial por partículas finas (opcional) <b>K</b>
	Revestimiento Excellence (KN Anti-Rayado/Anti-Niebla) <b>Sí</b>
	Puente nasal blando <b>Sí</b>
	Puntas blandas - Templo plano flexible sin presión <b>Sí</b>
	Peso del producto 29g

	<b>TRANSMISIÓN DE LA LUZ</b> Valor de oscurecimiento de lente 2,5
	Clase óptica (1- Clase 1- alta calidad para uso regular. 2 - Clase 2 - calidad media para uso ocasional. 3 - Clase 3- calidad baja para un uso excepcional). <b>1</b>
	La letra T, inmediatamente después del símbolo de resistencia mecánica, autoriza el uso de partículas de alta velocidad a temperaturas extremas. (-5° y +55°c) opcional <b>T</b>
	Resistencia al empañamiento (opcional) <b>N</b>
	Curva de la base de la lente <b>8</b>
	Ajuste de la nariz hacia arriba y hacia abajo <b>Sí</b>
	Tecnología Flexofit <b>Sí</b>



## CARACTERÍSTICAS

		<b>Anti-mist</b> Anti-mist			<b>Anti-scratch</b> Anti-scratch
		<b>Lens Curve</b> Lens curve			<b>High Performance Coating</b> Anti-scratch / anti-fog high performance coating
		<b>Rotating Arms</b> Rotating arms			<b>Soft End Tips</b> Soft end tips
		<b>Adjustable Nose Pad</b> Adjustable nose pad			<b>Flexofit Technology</b> Flexofit technology

## GAMA



## DESCARGAR

-  [Colección de imágenes \(ZIP\)](#)
-  [doc-lyss.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 6 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

