TECHNICAL SPECIFICATION

EVO®3 Mid Peak Revolution® Flex Wheel Ratchet Non Vented

Yellow / AJE170-000-200



DESCRIPTION

The EVO®3 Comfort Plus helmet combines a super strong shell for superior all day protection in the widest range of environments, with the comfort benefits of the new Evolution® 3D Adjustment™ harness system. EVO®3 is a true evolution of the long-established MK®2 and MK®3 helmets. The EVO®3 retains the JSP signature styling while incorporating developments first seen in the EVO®8. Packed full of the latest protection technology and features.

OPTIONS

Blue (AJE170-000-500)
Green (AJE170-000-300)
Grey (AJE170-000-400)
Orange (AJE170-000-800)
Red (AJE170-000-600)
White (AJE170-000-100)
Yellow (AJE170-000-200)

SAFETY STANDARDS

EN 397 • EN 50365

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Peak
Mid

EN 50365 ELECTRICAL INSULATION
1000V

Maximum Temperature
+50˚C

HDPE Shell
Yes

Textile
Harness

Wheel Ratchet
Yes

Ventilation
No

Integrated Eyewear
Optional

BSI Kitemark
Yes

Optional 4 point chinstrap (EN397 Compliant)
Optional

Product Weight
327g

ANSI ELECTRICAL CLASS E
20,000

Impact Resistance
50 Joules

Resistance to Molten Metals and Hot Solids (optional)
Yes

Minimum Temperature
-40˚C

Recyclable
Shell

Depth Adjustment
3D Harness

Universal Accessories Slot
Yes

Reflective Option
Optional

ID card holder
Optional

Optional 2 point chinstrap (EN397 & EN 812 compliant)
Optional

JSPCheck
Yes

Size
53-64cm

FEATURES



3D Adjustment

The comfortable textile harness features unique 1-2-3 point depth settings, offering the most precise fit attainable on an industrial safety helmet.



Accessories

A universal attachment slot enables firm fitting of a range of Surefit™ safety visors and ear defenders. EVOSpec® Integrated eyewear is also available.




JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.



CR2™ Reflective

Using Class RA2, high intensity reflective. CR2™ is the biggest step-up in night time visibility/reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



Supreme Comfort

A 6-point textile cradle harness system & Chamlon™ cotton sweatband offer unrivalled comfort.



Firmest fit available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. Available with either the Revolution® Flex wheel ratchet or the OneTouch™ slip ratchet.

LOGO

RANGE

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

- [x] Sides
- [x] Back
- [x] Front

VIDEOS

www.youtube.com/watch?v=PmDMMktdotQ
www.youtube.com/watch?v=LdxMNctXLbg

DOWNLOADS

Image Pack (ZIP)
doc-invincible-evo3.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.