

## EVO® ALTA™ Baseworker™

EVO® ALTA™ Baseworker™ (EN397) White Wheel Ratchet / ARA170-000-100



### BESCHREIBUNG

The new EVO® ALTA™ offers all-round impact protection. The mountaineering-style helmet features a specialised shell structure and internal liner to increase durability and shock absorption performance. Precise adjustment settings enable a secure fit, ensuring the helmet remains stable. Engineered to maximise compatibility and accessory integration, EVO® ALTA™ is an adaptive system with built-in attachment points and an interchangeable front module.

EVO® ALTA™ Baseworker™ offers the higher, all-round impact protection of an EN 12492 helmet with an EN 397 compliant chinstrap. The 4-point chinstrap is designed to release under force if caught or snagged. EVO® ALTA™ Baseworker™ is available in a non-vented version to provide EN 397 440V electrical insulation.

### OPTIONEN

**EVO® ALTA™ Baseworker™ (EN397) White Wheel Ratchet (ARB170-000-500)**

**EVO® ALTA™ Baseworker™ (EN397) White Wheel Ratchet (ARB170-000-300)**

**EVO® ALTA™ Baseworker™ (EN397) White Wheel Ratchet (ARB170-00C-700)**

**EVO® ALTA™ Baseworker™ (EN397) White Wheel Ratchet (ARB170-000-600)**

()

()

()

**EVO® ALTA™ Baseworker™ (EN397) Vented Wheel Ratchet ()**

**EVO® ALTA™ Baseworker™ (EN397) White Wheel Ratchet (ARA170-000-100)**

### SICHERHEITSSTANDARDS

EN 397 • EN 50365



## SPEZIFIKATIONEN

Schirm  
Mikro

Seitliche Schlagfestigkeit  
25 Joules

Seitliche Verformung  
Ja

EN 397 ELEKTRISCHE ISOLIERUNG  
440V (Non-vented only)

Min. Temperatur  
-40°C

EPP-Aufprall Absorber  
Ja

Textil  
Innenausstattung

Tiefeneinstellung  
3D-Anpassung

Fitted 4 point chinstrap (EN397 Compliant)  
Ausgestattet

Reflektierendes CR2  
Optional

JSPCheck  
Ja

Größe  
53-64cm

Stoßfestigkeit  
100 Joules

Schmelzmetall  
Ja

EN 50365 ELEKTRISCHE ISOLIERUNG  
1000V

Max. Temperatur  
+50°C

ABS-Schale  
Ja

Wiederverwendbar  
Schale

Belüftung  
Nein

Drehradverschluss  
Ja

Universeller Zubehör-Steckplatz  
Ja

ID-KARTENHALTER  
Optional

Produktgewicht  
500g

## EIGENSCHAFTEN



### All-Round Protection

EVO@ ALTA™ provides all-round impact protection with top, side, front and rear shock absorption performance. The helmet is designed with an extended nape section to offer greater neck coverage.



### Interchangeable Front Module

EVO@ ALTA™ features a unique interchangeable front module. Select the integrated ID card holder for on-site identification or choose the logo-ready standard front to apply company branding. Both front modules enable attachment of a helmet lamp and other accessories.



### Compatibility & Accessories

The EVO@ Alta™ range maximises compatibility and accessory integration. Attachment points on the helmet shell enable firm fitting of ear defenders, faceshields, goggle and lamp straps, plus a range of other accessories.



### EPP Liner

EVO@ ALTA™ features an internal impact liner to increase shock absorption and penetration protection. Manufactured in expanded polypropylene (EPP), the liner is lightweight and ventilated for comfort.



### Maximum Comfort

The Revolution@ Flex wheel ratchet harness secures the helmet, eliminating pressure points to provide maximum comfort. Fitted with a replaceable Chamlon™ cotton sweatband and fully compatible with EVO@ cooling sweatbands for protection against heat stress.



### Secure Fit

The harness cradles the head to keep the helmet stable with an adjustable 4-point chinstrap for increased security. 3D-Adjustment depth settings enable the most precise fit attainable on a safety helmet.

JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 22 Dec 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.





## 4-Point Chinstrap

The 4-point chinstrap is easy to adjust on the head. Size and anchorage point adjustment enable a tailored fit for different head sizes, ensuring stability and greater comfort.



## Custom Branding

Helmets can be customised to meet a corporate identity. Logo printing is available for the standard front module, helping to increase brand recognition and discourage theft. MOQs apply.

### LOGO

- Vorderseite
- Beidseitig

### SERIE



### DOWNLOADS

 [Bilderordner \(ZIP\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 22 Dec 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

