

# TECHNICAL SPECIFICATION



## EVO® ALTA™ Baseworker™

White / ARA170-000-100



### DESCRIPTION

The new EVO® ALTA™ range offers all-round impact protection. The mountaineering-style helmet features a specialised shell structure and internal liner to increase durability and shock absorption performance. Precise adjustment settings enable a secure fit, ensuring the helmet remains stable.

Engineered to maximise compatibility and accessory integration, the EVO® ALTA™ range is an adaptive system with built-in attachment points, and an interchangeable front module, and a selection of 4-point chinstraps for use in a wide range of applications.

EVO® ALTA™ Baseworker™ non vented meets the mandatory shock absorption and penetration resistance requirements of EN 12492 and is fully EN 397 compliant including an EN 397 compliant chinstrap. The 4-point chinstrap is designed to release under force if caught or snagged. EVO®ALTA™ Baseworker™ non vented meets the electrical insulation requirements of EN 397 and EN 50365:2002

### OPTIONS

Black (ARA170-001-100)  
Blue (ARA170-000-500)  
Extra Visibility Orange (ARA170-001-600)  
Extra Visibility Yellow (ARA170-00C-700)  
Green (ARA170-000-300)  
Red (ARA170-000-600)  
**White (ARA170-000-100)**

### SAFETY STANDARDS

EN 397 • EN 50365



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.
























Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 3 / Issued 3 Sep 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

	Peak Micro		Impact Resistance 100 Joules
	Side Impact Resistance 25 Joules		Molten Metal Yes
	Lateral Deformation Yes		EN 50365 ELECTRICAL INSULATION 1000V
	EN 397 ELECTRICAL INSULATION 440V (Non-vented only)		Maximum Temperature +50°C
	Minimum Temperature -40°C		ABS Shell Yes
	EPP Liner Yes		Recyclable Shell
	Textile Harness		Ventilation No
	Depth Adjustment 3D Harness		Wheel Ratchet Yes
	Fitted 4 point chinstrap (EN397 Compliant) Fitted		Universal Accessories Slot Yes
	Reflective Option Optional		ID card holder Optional
	JSPCheck Yes		Product Weight 500g
	Size 53-64cm		

## FEATURES



### All-Round Protection

EVO® ALTA™ provides all-round impact protection with top, side, front and rear shock absorption performance. The helmet is designed with an extended nape section to offer greater neck coverage.



### Interchangeable Front Module

EVO® ALTA™ features a unique interchangeable front module. Select the integrated ID card holder for on-site identification or choose the logo-ready standard front to apply company branding. Both front modules enable attachment of a helmet lamp and other accessories.



### Compatibility & Accessories

The EVO® ALTA™ range maximises compatibility and accessory integration. Attachment points on the helmet shell enable firm fitting of ear defenders, faceshields, goggle and lamp straps, plus a range of other accessories.



### EPP Liner

EVO® ALTA™ features an internal impact liner to increase shock absorption and penetration protection. Manufactured in expanded polypropylene (EPP), the liner is lightweight and ventilated for comfort.



### Maximum Comfort

The Revolution® Flex wheel ratchet harness secures the helmet, eliminating pressure points to provide maximum comfort. Fitted with a replaceable Chamlon™ cotton sweatband and fully compatible with EVO® cooling sweatbands for protection against heat stress.



### Secure Fit

The harness cradles the head to keep the helmet stable with an adjustable 4-point chinstrap for increased security. 3D-Adjustment depth settings enable the most precise fit attainable on a safety helmet.



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspafety.com / Web: www.jspafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 3 Sep 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.





## 4-Point Chinstrap

The 4-point chinstrap is easy to adjust on the head. Size and anchorage point adjustment enable a tailored fit for different head sizes, ensuring stability and greater comfort.



## Custom Branding

Helmets can be customised to meet a corporate identity. Logo printing is available for the standard front module, helping to increase brand recognition and discourage theft. MOQs apply.

### LOGO

- ☒ Front
- ☒ Sides

### RANGE



### DOWNLOADS

 [Image Pack \(ZIP\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 3 Sep 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

