TECHNICAL SPECIFICATION



EVO®5 DualSwitch™ Micro Peak Revolution® Wheel Ratchet Vented

Orange / AKS270-000-800



DESCRIPTION

JSP's EVO®5 DualSwitch™ is fully certified to both EN 397 and EN 12492, with the ability to change between the two standards easily at the flick of a switch.

JSP have delivered an innovative helmet which can be used at ground level (EN 397) or at height (EN 12492).

OPTIONS

Black (AKS270-001-100)

Blue (AKS270-000-500)

Orange (AKS270-000-800)

Red (AKS270-000-600)

White (AKS270-000-100)

SAFETY STANDARDS

EN 397 • EN 50365 • EN 12492 • ANSI/ISEA Z89.1 Type I











SPECIFICATIONS



Peak Micro



Side Impact Resistance 25 Joules



Lateral Deformation Yes



Maximum Temperature



+50°C



ABS Shell Yes



Recyclable Shell



Depth Adjustment 3D Harness



Universal Accessories Slot





Reflective Option

Optional



ID card holder

Optional



Fitted 4 point DualSwitch chinstrap (EN12492 and EN397 compliant)

Fitted



Product Weight

450g



Impact Resistance 100 Joules



EN 50365 ELECTRICAL INSULATION 1000V



Molten Metal

Yes



Minimum Temperature

-40°C



EPP Liner

Yes



Textile

Harness



Wheel Ratchet

Yes



Ventilation Yes



Integrated Eyewear

No



BSI Kitemark

Yes



JSPCheck

Yes



Size

53-64cm

FEATURES



Switch Down

The chinstrap release force of EN 12492 is greater than 500 Newtons. This limits the risk of losing the helmet during a fall.



EPP Liner

Our robust Expanded Polypropylene (EPP) liner ensures class leading impact attenuation, offering side, front and rear impact protection, as required in EN12492.



CR2

CR2 is the biggest step-up in night time visibility / reflectivity of head protection to date. A high intensity reflective material offering, on average, 60% more reflectivity than standard reflective clothing. CR2 is optional.



Switch Up

The chinstrap release force of EN 397 is between 150 and 250 Newtons. This limits the risk of choking, the chinstrap has been designed to release if snagged.



Secure fit

Featuring a fully adjustable 4-point chinstrap, easy to use Revolution® wheel ratchet and a 3D Adjustment harness, which offers 1-2-3 point depth settings for a perfect fit.



Accessories

Universal attachment slots enable fitting of Surefit™ safety visors and Sonis® ear defenders. EVOSpec® integrated eyewear. Lamp bracket & business card holder. The Visilite® helmet wearer illumination system can also be fitted to increase low light visibility.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.









Electrical Protection to 1000V



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.



Ventilation

The shell and EPP liner are vented to increase comfort and allow a cooling air flow, reducing helmet temperatures by an average 2-3 degrees.

Tough ABS Shell

The EVO®5 safety helmet features an extremely robust ABS shell designed for superior protection. It features a distinctive five stripe design and the JSP Shield, an internationally recognised symbol of quality.

LOGO

✓ Front

✓ Back

✓ Sides

RANGE



VIDEOS

www.youtube.com/watch?v=FHdlRqWkD3s

www.youtube.com/watch?v=pXBgCZzyGII

DOWNLOADS

Image Pack (ZIP)

doc-evo5-dualswitch.pdf (PDF)









Page 3 of 3 / Issued 2 Nov 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.





