

TECHNISCHE SPEZIFIKATION



5m automatischer Seileinzug

5m automatischer Seileinzug / FAR0705



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 17 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.





BESCHREIBUNG

Selbstaufrollende Rettungsleine aus 5 m Draht in einem robusten und langlebigen Kunststoffgehäuse, ausgestattet mit einem drehbaren Karabinerhaken aus Stahl und einem Aluminiumverbinder mit Schraubverschluss am Verankerungspunkt.

OPTIONEN

5m automatischer Seileinzug (FAR0705)

SICHERHEITSSTANDARDS

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 17 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 17 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



SPEZIFIKATIONEN

Sturzindikator
Ja

Material
Verzinkter Stahldraht mit einem Durchmesser von
4,5 mm

Scharfkantig
Nein

Bewertete Nennlast
140kg

Geliefert mit
1 drehbarer Stahlkarabinerhaken. Karabineröffnung
20mm. Entspricht EN362 Klasse T. 1 Aluminium-
Schraubkarabiner am Verankerungspunkt.
Karabineröffnung 22mm. Entspricht der EN362
Klasse B.

Länge
5m

Falldämpfer
Intern

Gehäuse
Robuster und langlebiger Kunststoff

Produktgewicht
2890g

ANWENDUNGEN

Nur allgemeine Hinweise und sollte nicht als Ersatz für eine vollständige Risikobeurteilung angesehen werden

Dokumente

Züge

DOWNLOADS

 [Bilderordner \(ZIP\)](#)

 [doc-far0705-far0706.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 17 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

