

TECHNISCHE SPEZIFIKATION



5m automatischer Seileinzug

5m automatischer Seileinzug / FAR0705



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jssafety.com / Web: www.jssafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jssafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 2 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





BESCHREIBUNG

Selbstaufrollende Rettungsleine aus 5 m Drahtseil in einem robusten und langlebigen Kunststoffgehäuse, ausgestattet mit einem drehbaren Karabinerhaken aus Stahl und einem Aluminiumverbinder mit Schraubverschluss am Verankerungspunkt.

OPTIONEN

5m automatischer Seileinzug (FAR0705)

SICHERHEITSSTANDARDS

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 2 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 2 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPEZIFIKATIONEN

Sturzindikator

Ja

Länge

5m

Material

Verzinkter Stahldraht mit einem Durchmesser von 4,5 mm

Falldämpfer

Intern

Scharfkantig

Nein

Gehäuse

Robuster und langlebiger Kunststoff



Bewertete Nennlast

140kg



Produktgewicht

2890g

Geliefert mit

1 drehbarer Stahlkarabinerhaken. Karabineröffnung 20mm. Entspricht EN362 Klasse T. 1 Aluminium-Schraubkarabiner am Verankerungspunkt. Karabineröffnung 22mm. Entspricht der EN362 Klasse B.

DOWNLOADS

 [Bilderordner \(ZIP\)](#)

 [doc-far0705-far0706.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 2 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

