

# TECHNICAL SPECIFICATION



## 5m Wire Self-Retractable Lifeline

5m Wire Self-Retractable Lifeline / FAR0705



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jssafety.com](mailto:sales@jssafety.com) / Web: [www.jssafety.com](http://www.jssafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jssafety.com](mailto:copyright@jssafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 26 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.





## DESCRIPTION

5m wire self-retractable lifeline in robust and durable plastic casing, equipped with steel swivel snap hook connector, and screw gate aluminium connector at anchorage point.

## OPTIONS

**5m Wire Self-Retractable Lifeline (FAR0705)**

## SAFETY STANDARDS

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 26 Sep 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 26 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

Fall Indicator  
Yes

Length  
5m

Material  
Galvanised Steel Wire 4.5mm Diameter

Shock Absorber  
Internal

Sharp Edge  
No

Casing  
Robust and Durable Plastic



Rated Weight / Load  
140kg



Product Weight  
2890g

Delivered With  
1 Steel Swivel Snap Hook. Gate Opening 20mm.  
Conforms to EN362 Class T. 1 Screw Gate  
Aluminium Connector At The Anchorage Point.  
Gate Opening 22mm. Conforms To EN362 Class B.

## APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Forms

Trains

## DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0705-far0706.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 26 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

