

## Limitatore di Caduta Auto-Retrattile, Cavo Metallico 5m

Limitatore di Caduta Auto-Retrattile, Cavo Metallico 5m / FAR0705



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jsp-safety.com](mailto:sales@jsp-safety.com) / Web: [www.jsp-safety.com](http://www.jsp-safety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jsp-safety.com](mailto:copyright@jsp-safety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 22 Nov 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.





## DESCRIZIONE

Limitatore di caduta autoretrattile con cavo da 5m in involucro di plastica robusto e durevole, dotato di moschettone girevole in acciaio e connettore in alluminio a vite nel punto di ancoraggio.

## OPZIONI

**Limitatore di Caduta Auto-Retrattile, Cavo Metallico 5m (FAR0705)**



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 22 Nov 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jgpsafety.com](mailto:sales@jgpsafety.com) / Web: [www.jgpsafety.com](http://www.jgpsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jgpsafety.com](mailto:copyright@jgpsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 22 Nov 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



## SPECIFICHE

Indicatore di Caduta  
Sì

Materiale  
Cavo d'acciaio galvanizzato 4.5mm di diametro

Spigoli Vivi

Peso Nominale / Carico  
140kg

Consegnato con  
1 Gancio a scatto girevole in acciaio. Apertura 20mm. Conforme a EN362 Classe T. 1 Connettore in alluminio a vite nel punto di ancoraggio. Apertura 22mm. Conforme a EN362 Classe B.

Lunghezza  
5m

Assorbitore  
Interno

Involucro  
Plastica robusta e durevole

Peso del Prodotto  
2890g

## APPLICAZIONI

Guida generale e non dovrebbe essere considerata un sostituto per una valutazione completa del rischio

Moduli

Ferroviario

## DOWNLOAD

 [Immagini Scaricabili \(ZIP\)](#)

 [doc-far0705-far0706.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jsp-safety.com](mailto:sales@jsp-safety.com) / Web: [www.jsp-safety.com](http://www.jsp-safety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jsp-safety.com](mailto:copyright@jsp-safety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 22 Nov 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

