

Limitatore di Caduta Auto-Retrattile, Cavo Metallico 5m

Limitatore di Caduta Auto-Retrattile, Cavo Metallico 5m / FAR0705



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jssafety.com / Web: www.jssafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jssafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 18 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





DESCRIZIONE

Limitatore di caduta autoretrattile con cavo da 5m in involucro di plastica robusto e durevole, dotato di moschettone girevole in acciaio e connettore in alluminio a vite nel punto di ancoraggio.

OPZIONI

Limitatore di Caduta Auto-Retrattile, Cavo Metallico 5m (FAR0705)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 18 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 18 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPECIFICHE

Indicatore di Caduta
Sì

Materiale
Cavo d'acciaio galvanizzato 4.5mm di diametro

Spigoli Vivi



Peso Nominale / Carico
140kg

Consegnato con
1 Gancio a scatto girevole in acciaio. Apertura 20mm. Conforme a EN362 Classe T. 1 Connettore in alluminio a vite nel punto di ancoraggio. Apertura 22mm. Conforme a EN362 Classe B.

Lunghezza
5m

Assorbitore
Interno

Involucro
Plastica robusta e durevole



Peso del Prodotto
2890g

DOWNLOAD

 [Immagini Scaricabili \(ZIP\)](#)

 [doc-far0705-far0706.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 18 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

