

Powercap® Active™ 8hr Multi Plug - Black

Schwarz / CAE601-941-100



BESCHREIBUNG

Powercap® Active™ ist ein leichtes Überdruck-Atmungsgerät zur Luftreinigung und Schutz gemäß EN812 für Anstoskappen. Firm-fitting and ergonomically designed, the Powercap® Active™ is designed to protect the user from dust and other airborne particulate pollutants to EN 12941 TH1P level.

OPTIONEN

Schwarz (CAE601-941-100)

SICHERHEITSTANDARDS

EN 12941 • EN 812



SPEZIFIKATIONEN

Schirm 7cm	Stoßfestigkeit 12 Joules x 4
Seitliche Schlagfestigkeit 12 Joules	Max. Temperatur +40°C
Min. Temperatur +5°C	HDPE-Schale Ja
Wiederverwendbar Schale	Schnallenartiges Gurtverstellungssystem Elastic harness with lockable buckle
Belüftung Ja	Reflektierendes CR2 Nein
Klassifizierung TH1 (Turbo hood)	Filtertyp P (Schützt gegen feste und flüssige Aerosole)
Anwendung R (Wiederverwendbar)	AUSATEMVENTIL Nein
Filtrationseffizienz 90%	Gesamte nach Innen gerichtete Leckage (TIL) 10% When fitted to PowerCap® Active™ respirator
Nominaler Schutzfaktor 10	UK Zugewiesener Schutzfaktor 10
Maskendesign Turbo hood Powered Air Purifying Respirator (Loose-fitting)	Gesichtsabdichtungs-Typ Hypoallergenic material
Latexfrei Ja	Metallfreie Nein
Filter-Lagerzeit 5 jahre	Filtermaterial Pleated media
Markenzeichen des Herstellers JSP Dolch	BSI Kitemark Ja
Produktgewicht 659g	Geräuschpegel 68.2dB
Batterie Typ Rechargeable Lithium-ion	4000mAh, 3.7V, 14.8Wh
Micro USB 5VDC, 1.0A	4.2VDC, 3.4A
8+ hours	5 hours approx.

EIGENSCHAFTEN



Powered Air

Protection to EN 12941 TH1P provides a cooling, comfortable supply of filtered air at 160 litres per minute, eliminating breathing resistance and visor misting.



Kopfschutz durch Anstoßkappe

The cap uses JSP HardCap™ A1+ bump cap technology, exceeding the EN 812 standard. The cap cover is easily removable, wipeable and machine washable.



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 24 Nov 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.





Micro USB Charging

PowerCap® Active™ is supplied with a micro USB cable for recharging in as little as 5 hours. The PowerBox™1 battery pack features a built-in fuel gauge, making it easy to check charge level.

ANWENDUNGEN

Nur allgemeine Hinweise und sollte nicht als Ersatz für eine vollständige Risikobeurteilung angesehen werden

Agrarwirtschaft

Flughäfen

Gebäudemanagement

Produktion

Maritim

Bahn und Tunnelbau

Einzelhändler

SERIE

VIDEOS



www.youtube.com/watch?v=L3NZePFx9Aw

www.youtube.com/watch?v=UhX3DJZfo6Q

DOWNLOADS

 [Bilderordner \(ZIP\)](#)

 [doc-powercap_active_ip.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 24 Nov 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

