

Powercap® Active™ 8hr Multi Plug - Black

Schwarz / CAE601-941-100



BESCHREIBUNG

Powercap® Active™ ist ein leichtes Überdruck-Atmungsgerät zur Luftreinigung und Schutz gemäß EN812 für Anstoskappen. Firm-fitting and ergonomically designed, the Powercap® Active™ is designed to protect the user from dust and other airborne particulate pollutants to EN 12941 TH1P level.

OPTIONEN















Schwarz (CAE601-941-100)

SICHERHEITSTANDARDS

EN 12941 • EN 812



SPEZIFIKATIONEN

	Schirm 7cm		Stoßfestigkeit 12 Joules x 4
	Seitliche Schlagfestigkeit 12 Joules		Max. Temperatur +40°C
	Min. Temperatur +5°C		HDPE-Schale Ja
	Wiederverwendbar Schale		Schnallenartiges Gurtverstellungssystem Elastic harness with lockable buckle
	Belüftung Ja		Reflektierendes CR2 Nein
	Klassifizierung TH1 (Turbo hood)		Filtertyp P (Schützt gegen feste und flüssige Aerosole)
	Anwendung R (Wiederverwendbar)		AUSATEMVENTIL Nein
	Filtrationseffizienz 90%		Gesamte nach Innen gerichtete Leckage (TIL) 10% When fitted to PowerCap® Active™ respirator
	Nominaler Schutzfaktor 10		UK Zugewiesener Schutzfaktor 10
	Maskendesign Turbo hood Powered Air Purifying Respirator (Loose-fitting)		Gesichtsabdichtungs-Typ Hypoallergenic material
	Latexfrei Ja		Metallfrei Nein
	Filter-Lagerzeit 5 Jahre		Filtermaterial Pleated media
	Markenzeichen des Herstellers JSP Dolch		BSI Kitemark Ja
	Produktgewicht 659g		Geräuschpegel 68.2dB
	Batterie Typ Rechargeable Lithium-ion		4000mAh, 3.7V, 14.8Wh
	Micro USB 5VDC, 1.0A		4.2VDC, 3.4A
	8+ hours		5 hours approx.
	Face Fit Testing Required Nein		

EIGENSCHAFTEN



Kopfschutz durch Anstoßkappe

The cap uses JSP HardCap™ A1+ bump cap technology, exceeding the EN 812 standard. The cap cover is easily removable, wipeable and



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 15 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





Powered Air

Protection to EN 12941 TH1P provides a cooling, comfortable supply of filtered air at 160 litres per minute, eliminating breathing resistance and visor misting.

machine washable.



Micro USB Charging

PowerCap® Active™ is supplied with a micro USB cable for recharging in as little as 5 hours. The PowerBox™1 battery pack features a built-in fuel gauge, making it easy to check charge level.

SERIE

VIDEOS



www.jspgo.com/UI-FH/UI_PowercapActive/UI_PowercapActive

DOWNLOADS

- [Bilderordner \(ZIP\)](#)
- [doc-powercap_active_ip.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspafety.com / Web: www.jspafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 15 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

