FICHE TECHNIQUE

Powercap® Active™ 8hr Multi Plug - Black

Noir / CAE601-941-100



DESCRIPTION

Powercap® Active™ is a lightweight powered air purifying respirator with EN 812 bump cap protection. Firm-fitting and ergonomically designed, the Powercap® Active™ is designed to protect the user from dust and other airborne particulate pollutants to EN 12941 TH1P level.

OPTIONS

Noir (CAE601-941-100)

NORMES

EN 12941 • EN 812

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

INFORMATIONS TECHNIQUES

Visière
7cm

Résistance aux chocs latéraux
12 Joules

Température Minimale
+5°C

Recyclable
Calotte:

Ventilation
Oui

Classification
TH1 (Turbo hood)

Utilisation
R (Réutilisable)

Efficacité de filtration minimale
90%

Facteur nominal de protection
10

Conception des masques
Turbo hood Powered Air Purifying Respirator (Loose-fitting)

Sans latex
Oui

Durée de stockage des filtres
5 ans

Marque du fabricant
JSP Dagger

Poids du produit
659g

Type de batterie
Rechargable Lithium-ion

Micro USB 5VDC, 1.0A

8+ hours

Résistance à l'impact
12 Joules x 4

Température Maximale
-40°C

Calotte PEHD
Oui

Serrage glissière
Glissière

Option réfléchissante
Non

Type de filtre
P (Protection contre les aérosols solides et liquides)

Valve d'expiration
Non

Fuite totale vers l'intérieur (TIL)
10% When fitted to PowerCap® Active™ respirator

Facteur de protection assigné au Royaume-Uni
10

Type de joint facial
Hypoallergenic material

Sans métal
Non

Matériau filtre
Pleated media

BSI Kitemark
Oui

Niveau sonore
68.2dB

4000mAh, 3.7V, 14.8Wh

4.2VDC, 3.4A

5 hours approx.

CARACTÉRISTIQUES



Powered Air

Protection to EN 12941 TH1P provides a cooling, comfortable supply of filtered air at 160 litres per minute, eliminating breathing resistance and visor misting.



Casquette anti-heurts

The cap uses JSP HardCap™ A1+ bump cap technology, exceeding the EN 812 standard. The cap cover is easily removable, wipeable and machine washable.

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



Micro USB Charging

PowerCap® Active™ is supplied with a micro USB cable for recharging in as little as 5 hours. The PowerBox™1 battery pack features a built-in fuel gauge, making it easy to check charge level.

GAMME

VIDÉOS

www.jspgo.com/UI-FH/UI_PowercapActive/UI_PowercapActive

TÉLÉCHARGEMENTS

Pack d'images (ZIP)

doc-powercap_active_ip.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.