

TECHNICAL SPECIFICATION



M600 Series - M632 - Box of 10 - FFP3V - MOULDED DISPOSABLE DUST MASK

M632 - - FFP3V - MOULDED DISPOSABLE DUST MASK / BGZ130-000-A00



DESCRIPTION

Moulded disposable respirator with comfort foam surround, adjustable nose clip, four-point adjustable harness and low resistance exhalation valve.

OPTIONS

**M632 - - FFP3V - MOULDED DISPOSABLE DUST MASK
(BGZ130-000-A00)**

SAFETY STANDARDS

EN 149

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jpsafety.com / Web: www.jpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 9 Jan 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Classification	FFP3 (Filtering Facepiece Particulate, Valved)		Filter Type	P (Protects Against Solid and Liquid Aerosols)
Usage	NR (Non-Reusable)		Activated Carbon Layer	No
Minimum Filtration Efficiency	99% For FFP3 Rated		Maximum Total Inward Leakage (TIL)	2%
Nominal Protection Factor			UK Assigned Protection Factor	20
50				
Mask Design	Moulded		Exhalation Valve	Yes - Polystyrene exhalation valve with rubber diaphragm
4 Point Harness adjustment system	Yes		Nose Bridge	Moulded in mask
Latex free	Yes		Mask Material	Polypropylene
Filter Shelf Life			Product Weight	22g (Approx) Each Mask
5 Years				

FEATURES



Exhalation Valve

Low resistance exhalation valve for easy breathing.



Foam Padded Nose Bridge

A mouldable nose bridge and 360° foam area around the inside provide comfort and a firmer fit.



4-Point Adjustable Straps

Metal free, 4-point adjustable straps create a firm and adaptable fit.

RANGE

M600
SERIES

DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-ce-m632.pdf \(PDF\)](#)