SPECYFIKACJA TECHNICZNA

Elastyczny pasek podbródkowy

Domyślnie / AHV001-100-000



OPIS

Elastyczny pasek podbródkowy, zwalnia się automatycznie przy siłach pomiędzy 150 a 250 niutonów.

OPCJE

Domyślnie (AHV001-100-000)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECYFIKACJE

Typ
Standardowy

GAMA

HEAD
ACCESSORIES

PLIKI DO POBRANIA

Zbiór zdjęć (ZIP)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.