# TECHNICAL SPECIFICATION



## MARTCARE® M Series

MARTCARE® M Series Moulded Disposable Mask - Box of 10 - M32 - FFP3V / BEH130-002-A00



#### DESCRIPTION

The Martcare® range offers a cost-effective solution, with a straightforward selection of easy-to-use PPE, subject to the rigorous batch testing and conformity procedures applicable to the entire JSP PPE range.

#### OPTIONS

MARTCARE® M Series Moulded Disposable Mask - Box of 10 - M22 - FFP2V (BEH120-002-A00)

# MARTCARE® M Series Moulded Disposable Mask - Box of 10 - M32 - FFP3V (BEH130-002-A00)

MARTCARE® M Series Moulded Disposable Mask - Box of 20 - M21 - FFP2 (BEG120-002-B00)

MARTCARE® M Series Moulded Disposable Mask - Box of 20 - M31 - FFP3 (BEG130-002-B00)

SAFETY STANDARDS

EN 149



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



#### SPECIFICATIONS

No

Classification FFP3 (Filtering Facepiece Particulate, Valved)

Usage NR (Non-Reusable)



Activated Carbon Layer

Maximum Total Inward Leakage (TIL) 2%

UK Assigned Protection Factor 20



Exhalation Valve Yes - Polystyrene exhalation valve with rubber diaphragm

Mask Material Polypropylene



Product Weight 16g (Approx)

#### FEATURES



#### Inner Foam Nose Bridge

Foam padding around the nose area of the mask provides comfort and a firmer fit.



#### **Metal Free Straps**

Mask straps ultrasonically welded ensuring no metal parts in contact with the face.



#### **Exhalation Valve**

Low resistance exhalation valve for easy breathing.

### RANGE



### DOWNLOADS

Image Pack (ZIP)

doc-disposable-dust-masks-martcare-m-series-m32.pdf (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



Filter Type
P (Protects Against Solid and Liquid Aerosols)



(D) Resistance to dust clogging Yes - D marking = passes optional clogging test

Minimum Filtration Efficiency 99% For FFP3 Rated

Nominal Protection Factor 50

Mask Design Moulded

 $\overline{\bigcirc}$ 

Nose Bridge Moulded in mask

Filter Shelf Life 5 Years