

# TECHNICAL SPECIFICATION



## MARTCARE® M Series

MARTCARE® M Series Moulded Disposable Mask - Box of 10 - M32 - FFP3V / BEH130-002-A00



### DESCRIPTION

The Martcare® range offers a cost-effective solution, with a straightforward selection of easy-to-use PPE, subject to the rigorous batch testing and conformity procedures applicable to the entire JSP PPE range.

### OPTIONS

MARTCARE® M Series Moulded Disposable Mask - Box of 10 - M22 - FFP2V (BEH120-002-A00)

**MARTCARE® M Series Moulded Disposable Mask - Box of 10 - M32 - FFP3V (BEH130-002-A00)**

MARTCARE® M Series Moulded Disposable Mask - Box of 20 - M21 - FFP2 (BEG120-002-B00)

MARTCARE® M Series Moulded Disposable Mask - Box of 20 - M31 - FFP3 (BEG130-002-B00)

### SAFETY STANDARDS

EN 149



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsspsafety.com / Web: www.jsspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 5 Oct 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

Classification  
FFP3 (Filtering Facepiece Particulate, Valved)

Usage  
NR (Non-Reusable)

Activated Carbon Layer  
No

Maximum Total Inward Leakage (TIL)  
2%

UK Assigned Protection Factor  
20

Exhalation Valve  
Yes - Polystyrene exhalation valve with rubber diaphragm

Mask Material  
Polypropylene

Product Weight  
16g (Approx)

Filter Type  
P (Protects Against Solid and Liquid Aerosols)

(D) Resistance to dust clogging  
Yes - D marking = passes optional clogging test

Minimum Filtration Efficiency  
99% For FFP3 Rated

Nominal Protection Factor  
50

Mask Design  
Moulded

Nose Bridge  
Moulded in mask


Filter Shelf Life  
5 Years

## FEATURES




### Inner Foam Nose Bridge

Foam padding around the nose area of the mask provides comfort and a firmer fit.



### Metal Free Straps

Mask straps ultrasonically welded ensuring no metal parts in contact with the face.



### Exhalation Valve

Low resistance exhalation valve for easy breathing.

## APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Aerospace

Agricultural

Airports

Construction and Infrastructure

Facilities Management

Food and Drink Manufacturing

Forestry & Landscaping

Hospitals, Healthcare & Pharmaceuticals

Law Enforcement

Manufacturing

Renewable, Wind and Solar Energy

Scaffolding and Roofing

Sole Trader

Transportation, Warehousing & Logistics


Utilities Contractors

## RANGE



## DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-disposable-dust-masks-martcare-m-series-m32.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 5 Oct 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.

