

# TECHNICAL SPECIFICATION



## Swiss One LYSS

1LYSBB23CKN / 1LYSBB23CKN



### DESCRIPTION

Discover the new Eyewear generation... Lyss™ eyewear with Swiss One Flexofit technology... Angle adjustable nose pad for exceptional fit and adjustment for any situation... Worker comfort for many facial profiles. Soft cushioning browguard, pantoscopic temples with 3 side inclination positions and a unique up and down inclinable nose bridge concept to fit all nose shapes. THE fully adjustable spectacle!

### OPTIONS

**1LYSBB23CKN (1LYSBB23CKN)**

1LYSBY23CKN (1LYSBY23CKN)

1LYSDG23CKN (1LYSDG23CKN)

1LYSDG23SKN (1LYSDG23SKN)

### SAFETY STANDARDS

EN 170 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jsp-safety.com](mailto:sales@jsp-safety.com) / Web: [www.jsp-safety.com](http://www.jsp-safety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jsp-safety.com](mailto:copyright@jsp-safety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 15 Dec 2025 / Copyright 2018 - 2025, JSP Limited. All Rights Reserved.



## SPECIFICATIONS



**RADIATION PROTECTION BREAKDOWN** filtering effect  
Scale Number  
2C



Manufacture's Trademark Swiss One  
**Swiss One**



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °  
Maximum protection for glasses  
**F**



Resistance to Surface Damage by Fine Particles (optional)  
**K**

Excellence Coating (KN Anti-Scratch/Anti-Mist)  
**Yes**

Soft Nose Pad  
**Yes**

Soft End Tips - Flex Flat Temple Pressure Free  
**Yes**



Product Weight  
29g



**LIGHT TRANSMISSION BREAKDOWN** Lens Shade number  
1.2



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)  
**1**



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional  
**T**



Resistance to fogging (optional)  
**N**

Lens Base Curve  
**8**

Up And Down Nose Adjustment  
**Yes**

FLEXoFIT Technology  
**Yes**

## FEATURES



### Anti-mist

Anti-mist



### Lens Curve

Lens curve



### Rotating Arms

Rotating arms



### Adjustable Nose Pad

Adjustable nose pad



### Anti-scratch

Anti-scratch



### High Performance Coating

Anti-scratch / anti-fog high performance coating



### Soft End Tips

Soft end tips



### Flexofit Technology

Flexofit technology

## RANGE



## DOWNLOADS



[Image Pack \(ZIP\)](#)



[doc-lyss.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 15 Dec 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

