

ESPECIFICACIONES TÉCNICAS



Swiss One LYSS

1LYSBB23CKN / 1LYSBB23CKN



DESCRIPCIÓN

Discover the new Eyewear generation... Lyss™ eyewear with Swiss One Flexofit technology... Angle adjustable nose pad for exceptional fit and adjustment for any situation... Worker comfort for many facial profiles. Soft cushioning browguard, pantoscopic temples with 3 side inclination positions and a unique up and down inclinable nose bridge concept to fit all nose shapes. THE fully adjustable spectacle!

OPCIONES

1LYSBB23CKN (1LYSBB23CKN)

1LYSBY23CKN (1LYSBY23CKN)

1LYSDG23CKN (1LYSDG23CKN)

1LYSDG23SKN (1LYSDG23SKN)

NORMAS DE SEGURIDAD

EN 170 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 15 Dec 2025 / Copyright 2018 - 2025, JSP Limited. All Rights Reserved.



ESPECIFICACIONES



PROTECCIÓN RADIOLÓGICA Valor de escala de efecto de filtrado
2C



Marca del fabricante Swiss One
Swiss One



El impacto de baja energía resiste una bola de 6 mm, 0,86 g a 45 m/s de Máxima protección para gafas
F



Resistencia al daño superficial por partículas finas (opcional)
K

Revestimiento Excellence (KN Anti-Rayado/Anti-Niebla)
Sí

Puente nasal blando
Sí

Puntas blandas - Templo plano flexible sin presión
Sí



Peso del producto
29g



TRANSMISIÓN DE LA LUZ Valor de oscurecimiento de lente
1,2



Clase óptica (1- Clase 1- alta calidad para uso regular. 2 - Clase 2 - calidad media para uso ocasional. 3 - Clase 3- calidad baja para un uso excepcional).
1



La letra T, inmediatamente después del símbolo de resistencia mecánica, autoriza el uso de partículas de alta velocidad a temperaturas extremas. (-5° y +55°c) opcional
T



Resistencia al empañamiento (opcional)

Curva de la base de la lente
8

Ajuste de la nariz hacia arriba y hacia abajo
Sí

Tecnología Flexofit
Sí

CARACTERÍSTICAS



Anti-mist

Anti-mist



Lens Curve

Lens curve



Rotating Arms

Rotating arms



Adjustable Nose Pad

Adjustable nose pad



Anti-scratch

Anti-scratch



High Performance Coating

Anti-scratch / anti-fog high performance coating



Soft End Tips

Soft end tips



Flexofit Technology

Flexofit technology

GAMA



DESCARGAR



[Colección de imágenes \(ZIP\)](#)



[doc-lyss.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 15 Dec 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

