

TECHNICAL SPECIFICATION



Helmet Lanyard

Helmet Lanyard / FAR0512



DESCRIPTION

Lanyard used to tether helmets, PPE items or small hand tools to prevent falling objects when working at height.

The elastic lanyard is made with a durable high-stretch elastic material. With a quick connect clamp on one end, it can be easily and securely attached, even while wearing gloves.

OPTIONS

Helmet Lanyard (FAR0512)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 12 Dec 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.



SPECIFICATIONS

Length
0.48m to 1.22m



Rated Weight / Load
0.9kg (Helmet)

Material
Comfortable Durable High Stretch Elastic Material

Delivered With
Quick Connect Clamp That Attaches Securely To Fabric

DOWNLOADS

 [Image Pack \(ZIP\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jssafety.com / Web: www.jssafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jssafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 12 Dec 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

