

## Ośłona octanowa Surefit™ - 20 cm

Ośłona octanowa Surefit™ - 20 cm / ANX010-230-000



### OPIS

Wymienna osłona octanowa do Surefit™.

### OPCJE

**Ośłona octanowa Surefit™ - 20 cm (ANX010-230-000)**

### NORMY BEZPIECZEŃSTWA

EN 166 • AS/NZS 1337.1



## SPECYFIKACJE



Znak towarowy producenta

Charakterystyczny Sztylet JSP



Odporność na uderzenia o niskiej energii jest odporna na kulkę 6 mm, 0.86 g przy 45 m/s. Maksymalna ochrona okularów.

F



Długość wizjera

20cm



Nadaje się do recyklingu

Tak



Klasa optyczna (1 - klasa 1 - wysoka jakość do regularnego użytkowania. 2 - klasa 2 - średnia jakość do sporadycznego użytku. 3 - klasa 3 - niska jakość do wyjątkowych zastosowań)

1



Ochrona przed rozpryskami cieczy

3

Materiał

Octan

## GAMA

# SUREFIT

## PLIKI DO POBRANIA

[Zbiór zdjęć \(ZIP\)](#)

[doc-surefit-helmet-mounted-faceshields-updated-nb2797.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 14 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

