

Spartan™ 2m Single Fall Arrest Lanyard with Scaffold Hook

Spartan™ 2m Single Fall Arrest Lanyard with Scaffold Hook / FAR0305



DESCRIPTION

Spartan™ fall arrest lanyards are manufactured in 33mm flat webbing with steel connectors. Complete with karabiner and scaffold hook.

OPTIONS

Spartan™ 2m Single Fall Arrest Lanyard with Scaffold Hook (FAR0305)

SAFETY STANDARDS

EN 355



SPECIFICATIONS

Fall Indicator
Yes

Length
2m

Material
30mm Polyester Webbing With Textile Loops On Both Ends.

Shock Absorber
External

Sharp Edge
No

Rope Ends
X

Protective Rope Sleeve
No



Product Weight
1100g

Delivered With
1 Screw Gate Connector In Alloy Steel. Gate Opening 18mm. Conforms to EN362 Class B & M. 1 Alloy Steel Scaffold Hook. Gate Opening 50mm. Conforms to EN362 Class T.

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Ventilation

DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0305-far0317-far0309.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 15 Dec 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.

