TECHNICAL SPECIFICATION



Spartan™ 2m Single Fall Arrest Lanyard with Scaffold Hook

Spartan™ 2m Single Fall Arrest Lanyard with Scaffold Hook / FAR0305



DESCRIPTION

Spartan[™] fall arrest lanyards are manufactured in 33mm flat webbing with steel connectors. Complete with karabiner and scaffold hook.

OPTIONS

Spartan[™] 2m Single Fall Arrest Lanyard with Scaffold Hook (FAR0305)

SAFETY STANDARDS

EN 355















SPECIFICATIONS

Fall Indicator

Yes

Material

30mm Polyester Webbing With Textile Loops On

Both Ends.

Sharp Edge

No

Protective Rope Sleeve

No

Delivered With

1 Screw Gate Connector In Alloy Steel. Gate Opening 18mm. Conforms to EN362 Class B & M. 1 Alloy Steel Scaffold Hook. Gate Opening 50mm. Conforms to EN362 Class T.

Length 2m

Shock Absorber External

Rope Ends



Product Weight

1100g

Χ

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Ventilation

DOWNLOADS



Image Pack (ZIP)



doc-far0305-far0317-far0309.pdf (PDF)









