

Replacement Integrated Lens for EVO® VISTAlens®

Replacement Integrated Lens for EVO® VISTAlens® / AMV250-000-000



DESCRIPTION

Replacement Integrated Over Moulded Anti Mist Anti Scratch KN Lens for EVO®VISTAlens® Helmet

OPTIONS

EVO® VISTA® Replacement B Rated Clear Lens (AMV250-000-000)

Replacement Integrated Lens for EVO® VISTAlens® (AMV250-000-000)

EVO® VISTA® Replacement B Rated Indoor/Outdoor Lens (AMV150-000-000)

SAFETY STANDARDS

EN 170 • EN 166



SPECIFICATIONS



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
2C



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.2



Manufacturer's Trademark
JSP Dagger



Optical Class (1 – Class 1 – High quality for regular use. 2 –
Class 2 – Medium quality for occasional use. 3 – Class 3 –
Low quality for exceptional use)
1



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120
m/s Maximum protection for goggles.
B



The letter T, immediately after the mechanical strength
symbol, authorises use for high speed particles at extreme
temperatures. (-5°C and +55°C) Optional
T



Resistance to Surface Damage by Fine Particles (optional)
K



Resistance to fogging (optional)
N



Product Weight
79g

Material
Polycarbonate

Material
TPE Seal



Recyclable
Yes

Lens Length
9.5cm



BSI Kitemark
Yes

VIDEOS

www.youtube.com/watch?v=i8-pUlr11o

DOWNLOADS

[Image Pack \(ZIP\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 4 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

