

# TECHNISCHE SPEZIFIKATION



## 5m Höhengsicherungsgerät mit Stahlseil - Kantengeeignet

5m Höhengsicherungsgerät mit Stahlseil - Kantengeeignet / FAR0720



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jssafety.com](mailto:sales@jssafety.com) / Web: [www.jssafety.com](http://www.jssafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jssafety.com](mailto:copyright@jssafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 17 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.





## BESCHREIBUNG

Selbstaufrollende Rettungsleine aus 5 m Draht in einem robusten und langlebigen Kunststoffgehäuse, ausgestattet mit einem drehbaren Karabinerhaken aus Stahl und einem Aluminiumverbinder mit Schraubverschluss am Verankerungspunkt. Geeignet für horizontalen

## OPTIONEN

### 5m Höhengsicherungsgerät mit Stahlseil - Kantengeeignet (FAR0720)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jssafety.com / Web: www.jssafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jssafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 17 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.





JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jgpsafety.com](mailto:sales@jgpsafety.com) / Web: [www.jgpsafety.com](http://www.jgpsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jgpsafety.com](mailto:copyright@jgpsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 17 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



## SPEZIFIKATIONEN

Sturzindikator

Ja

Material

Verzinkter Stahldraht mit 4,8mm Durchmesser

Scharfkantig

Ja

Bewertete Nennlast

100kg

Geliefert mit

1 drehbarer Stahlkarabinerhaken. Karabineröffnung 20mm. Entspricht EN362 Klasse T. 1 Aluminium-Schraubkarabiner am Verankerungspunkt. Karabineröffnung 22mm. Entspricht der EN362 Klasse B.

Länge

5m

Falldämpfer

Außen

Gehäuse

Robuster und langlebiger Kunststoff

Produktgewicht

3114g

## DOWNLOADS

 [Bilderordner \(ZIP\)](#)

 [doc-far0720-far0721.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jssafety.com](mailto:sales@jssafety.com) / Web: [www.jssafety.com](http://www.jssafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jssafety.com](mailto:copyright@jssafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 17 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

