

# TECHNICAL SPECIFICATION



## 5m Wire Self-Retractable Lifeline Sharp Edge

5m Wire Self-Retractable Lifeline Sharp Edge / FAR0720



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 13 Dec 2025 / Copyright 2018 - 2025, JSP Limited. All Rights Reserved.





## DESCRIPTION

5m wire self-retractable lifeline in robust and durable plastic casing, equipped with steel swivel snap hook connector, and screw gate aluminium connector at anchorage point. Suitable for horizontal use (VG 11 RFU CNB/P/11.060).

## OPTIONS

**5m Wire Self-Retractable Lifeline Sharp Edge (FAR0720)**

## SAFETY STANDARDS

EN 360



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jsp-safety.com](mailto:sales@jsp-safety.com) / Web: [www.jsp-safety.com](http://www.jsp-safety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jsp-safety.com](mailto:copyright@jsp-safety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 13 Dec 2025 / Copyright 2018 - 2025, JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 13 Dec 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

Fall Indicator  
**Yes**

Length  
**5m**

Material  
**Galvanised Steel Wire 4.8mm Diameter**

Shock Absorber  
**External**

Sharp Edge  
**Yes**

Casing  
**Robust and Durable Plastic**



Rated Weight / Load  
**100kg**



Product Weight  
**3114g**

Delivered With  
1 Steel Swivel Snap Hook. Gate Opening 20mm.  
Conforms To EN362 Class T. 1 Screw Gate  
Aluminium Connector At The Anchorage Point.  
Gate Opening 22mm. Conforms To EN362 Class B.

## DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0720-far0721.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 13 Dec 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

