

# ESPECIFICACIONES TÉCNICAS



## Línea de vida auto-retráctil de alambre de 5 m con borde afilado

Línea de vida auto-retráctil de alambre de 5 m con borde afilado / FAR0720



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 18 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





## DESCRIPCIÓN

Línea de vida auto-retráctil de alambre de 5m en carcasa de plástico robusta y duradera, equipada con conector de gancho giratorio de acero y conector de aluminio de puerta de tornillo en el punto de anclaje. Adecuado para uso horizontal (VG 11 RFU CNB P/11.060).

## OPCIONES

**Línea de vida auto-retráctil de alambre de 5 m con borde afilado (FAR0720)**



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jssafety.com / Web: www.jssafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jssafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 18 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 18 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



## ESPECIFICACIONES

Indicador de caída  
Sí

Material  
Alambre de acero galvanizado de 4,8 mm de diámetro

Borde afilado  
Sí



Peso/carga nominal  
100kg

Se entrega con  
1 gancho con cierre de seguridad giratorio de acero. Apertura del gatillo: 20 mm. Conforme a EN 362 Clase T. 1 conector de aluminio con cierre de rosca en el punto de anclaje. Apertura del gatillo: 22 mm. Conforme a EN 362 Clase B.

Longitud  
5m

Absorbedor  
Externo

Carcasa  
Carcasa de plástico robusta y duradera



Peso del producto  
3114g

## DESCARGAR

 [Colección de imágenes \(ZIP\)](#)

 [doc-far0720-far0721.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 18 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

