

TECHNISCHE SPECIFICATIES



5m draad zelfoprolbare veiligheidslijn met scherpe rand

5m draad zelfoprolbare reddingslijn met scherpe rand / FAR0720



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 4 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





BESCHRIJVING

5m draad zelfoprolbare leeflijn in robuuste en duurzame kunststof behuizing, uitgerust met stalen draaibare karabijnhaak connector en aluminium schroefpoort connector op verankeringspunt. Geschikt voor horizontaal gebruik (VG 11 RFU CNB/P/11.060).

OPTIES

5m draad zelfoprolbare reddingslijn met scherpe rand (FAR0720)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jssafety.com / Web: www.jssafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jssafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 4 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 4 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPECIFICATIES

Valindicator
Ja

Materiaal
Gegalvaniseerde staaldraad met een diameter van
4,8 mm

Scherpe rand
Ja



Nominaal gewicht / belasting
100 kg

Geleverd met
1 Stalen draaibare karabijnhaak. Poortopening 20
mm. Voldoet aan EN362 Klasse T. 1 Aluminium
schroefverbinding bij het verankeringspunt.
Poortopening 22 mm. Voldoet aan EN362 Klasse B.

Lengte
5m

Schokdemper
Extern

Behuizing
Robuust en duurzaam plastic



Gewicht product
3114g

DOWNLOADS

 [Pakket afbeeldingen \(ZIP\)](#)

 [doc-far0720-far0721.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jssafety.com / Web: www.jssafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jssafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 4 of 4 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

