TECHNICAL SPECIFICATION



10m Rope & Grab

10m Rope & Grab / FAR0810



DESCRIPTION

Fall Arrest system with 12mm diameter kernmantle rope anchorage line and non-openable stainless steel rope grab equipped with energy absorber. The anchorage line has one connector, with the other end folded back and stitched 10cm.

OPTIONS

10m Rope & Grab (FAR0810)

SAFETY STANDARDS

EN 353-2



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Fall Indicator

Material 12mm Kernmantle Rope

Rope Ends 1 Side 1 Connector and. Other Side Folded Back and Stitched 10cm.

Adjustment Device Non-Openable Stainless Steel Rope Grab

Delivered With 2 Screwgate Connectors In Alloy Steel. Gate

Opening 18mm. Conforms to EN362 Class B & M

DOWNLOADS

Image Pack (ZIP)

doc-far0810-far0811-far0812.pdf (PDF)

Length 10m

Shock Absorber External

Protective Rope Sleeve No

|--|

Product Weight 2110g



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.