

10m lina z chwytakiem

10m lina z chwytakiem / FAR0810



OPIS

System zabezpieczenia przed upadkiem z liną kotwiczącą wykonaną z kernmantle o średnicy 12 mm i nieotwieralnym chwytakiem linowym ze stali nierdzewnej wyposażonym w absorber energii. Linka kotwicząca ma jeden zatrzaśnik, a drugi koniec jest zagięty do tyłu i zszyty na długości 10 cm.

OPCJE

10m lina z chwytakiem (FAR0810)

NORMY BEZPIECZEŃSTWA

EN 353-2



SPECYFIKACJE

Wskaźnik upadku
Nie

Materiał
Lina Kernmantle 12mm

Końce lin
1 strona 1 Zatrzaśnik a druga strona złożona do tyłu i zszyta 10cm.

Urządzenie regulacyjne
Nieotwieralny chwytak linowy ze stali nierdzewnej

Dostarczane z
2 zatrzaśniki śrubowe ze stali stopowej Otwarcie 18mm. Zgodny z EN362 Klasa B i M

Długość
10m

Amortyzator
Zewnętrzna

Rękaw ochronny liny
Nie



Waga Produktu
2110g

PLIKI DO POBRANIA

 [Zbiór zdjęć \(ZIP\)](#)

 [doc-far0810-far0811-far0812.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 20 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

