# TECHNICAL SPECIFICATION



## K2™ 2m Single Fall Arrest Lanyard

K2™ 2m Single Fall Arrest Lanyard / FAR0404



#### DESCRIPTION

The K2<sup>™</sup> internal fall arrest lanyards come with the energy absorption feature incorporated within their core. Without the need for an extra energy absorption pack, they are lighter in weight than other solutions, and also prevent trip hazards.

The elastic nature of these lanyards reduce the actual effective length of the lanyard, and it is therefore important to note both lanyard length and effective length.

### OPTIONS

K2™ 2m Single Fall Arrest Lanyard (FAR0404)

#### SAFETY STANDARDS

EN 355















#### **SPECIFICATIONS**

Fall Indicator

No

Material

40mm Wide Tubular Polyester Webbing With

Textile Loops.

Sharp Edge

No

Protective Rope Sleeve

No

**Delivered With** 

1 Quarter Turn Aluminium Connector. Gate

Opening: 21mm. Conforms To EN362:2004 Class B 1 aluminium scaffold hook. Gate Opening 60 mm.

Conforms To EN362:2004 Class A/T

Length 1.4m to 2m

Shock Absorber

Internal

Rope Ends

Χ



**Product Weight** 

989g

#### **APPLICATIONS**

General guidance only and should not be considered a substitute for a full risk assessment

Ventilation

#### DOWNLOADS



Image Pack (ZIP)



doc-far0404-far0405.pdf (PDF)







