TECHNICAL SPECIFICATION



K2™ 2m Single Fall Arrest Lanyard

K2™ 2m Single Fall Arrest Lanyard / FAR0404



DESCRIPTION

The K2[™] internal fall arrest lanyards come with the energy absorption feature incorporated within their core. Without the need for an extra energy absorption pack, they are lighter in weight than other solutions, and also prevent trip hazards.

The elastic nature of these lanyards reduce the actual effective length of the lanyard, and it is therefore important to note both lanyard length and effective length.

OPTIONS

K2™ 2m Single Fall Arrest Lanyard (FAR0404)

SAFETY STANDARDS

EN 355















SPECIFICATIONS

Fall Indicator

No

Material

40mm Wide Tubular Polyester Webbing With Textile Loops.

Sharp Edge

No

Protective Rope Sleeve

No

Delivered With

1 Quarter Turn Aluminium Connector. Gate

Opening: 21mm. Conforms To EN362:2004 Class B 1 aluminium scaffold hook. Gate Opening 60 mm.

Conforms To EN362:2004 Class A/T

Length 1.4m to 2m

Shock Absorber

Internal

Rope Ends

Χ



Product Weight

989g

DOWNLOADS









JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





