

ESPECIFICACIONES TÉCNICAS



Mosquetón de aluminio de triple bloqueo

Mosquetón de aluminio de triple bloqueo / FAR0941



DESCRIPCIÓN

Conector de cierre automático y bloqueo automático. Carga de rotura de 23kN.

OPCIONES

Mosquetón de aluminio de triple bloqueo (FAR0941)

NORMAS DE SEGURIDAD

EN 362



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 25 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



ESPECIFICACIONES

Material
Aluminio

Apertura
21 mm



Peso del producto
79g

Tipo de conector
Cierre automático y triple bloqueo automático



Peso/carga nominal
Carga de rotura 23KN

DESCARGAR

 [Colección de imágenes \(ZIP\)](#)

 [doc-far0904-far0905-far0941.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 25 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

