


TECHNICAL SPECIFICATION



Swiss One LEONE

1LEOCARB23S / 1LEOCARB23S



DESCRIPTION

Elegance & performance to deliver an optimal safety spectacle. Perfectly contoured for optimal fit without pressure. A 9 base curve providing excellent side coverage and maximum peripheral vision. Forget safety, enjoy the fit and features of stylish protective eyewear!

OPTIONS

1LEO21SVAR (1LEO21SVAR)
1LEO23C (1LEO23C)
1LEO23S (1LEO23S)
1LEOCARB21SPOL (1LEOCARB21SPOL)
1LEOCARB23S (1LEOCARB23S)

SAFETY STANDARDS

EN 172 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 17 Sep 2025 / Copyright 2018 - 2025, JSP Limited. All Rights Reserved.



SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect
Scale Number
5



Manufacture's Trademark Swiss One
Swiss One



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °
Maximum protection for glasses
F



Resistance to Surface Damage by Fine Particles (optional)
K

Excellence Coating (KN Anti-Scratch/Anti-Mist)
Yes

Lightweight
Yes

Soft End Tips - Flex Flat Temple Pressure Free
Yes



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
2.5



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional
T



Resistance to fogging (optional)
N

Lens Base Curve
9

Soft Nose Pad
Yes



Product Weight
24g

FEATURES



Anti-mist

Anti-mist



UV 400 Absorption

UV 400 absorption



High Performance Coating

Anti-scratch / anti-fog high performance coating



Soft Nose Pad

Soft nose pad



Anti-scratch

Anti-scratch



Lens Curve

Lens curve



Lightweight

Lightweight



Soft End Tips

Soft end tips

RANGE



DOWNLOADS



[Image Pack \(ZIP\)](#)



[doc-leone.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 17 Sep 2025 / Copyright 2018 - 2025, JSP Limited. All Rights Reserved.

