

# TECHNICAL SPECIFICATION



## Flexinet® Mask FFP3 Valved (832)

Box of 5 / BER130-001-M00



### DESCRIPTION

The Flexinet™ disposable mask has an ergonomic 3D design to fit most face shapes, with extremely low breathing resistance and mesh outer shell to help the mask retain its shape.

- High efficiency (99% minimum) filtering.

### OPTIONS

**Box of 5 (BER130-001-M00)**

### SAFETY STANDARDS

EN 149



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 15 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

Classification  
FFP3 (Filtering Facepiece Particulate)

Usage  
NR (Non-Reusable)



Activated Carbon Layer  
No

Maximum Total Inward Leakage (TIL)  
2%

UK Assigned Protection Factor  
20



Exhalation Valve  
Advanced Valve



Nose Bridge  
Moulded

Metal Free  
Yes

Filter Shelf Life  
5 Years



Product Weight  
26g



Filter Type  
P (Protects Against Solid and Liquid Aerosol)



(D) Resistance to dust clogging  
Yes – D marking = passes optional clogging test

Minimum Filtration Efficiency  
99% For FFP3 Rated

Nominal Protection Factor  
50

Mask Design  
Mesh Outer Shell



4 Point Harness adjustment system  
Yes

Latex free  
No


Mask Material  
Polypropylene



BSI Kitemark  
Yes

Face Fit Testing Required  
Yes

## FEATURES



### Comfort

A 360° comfort foam area around the inside of the mask provides a perfect fit.



### Advanced Valve

Advanced design valve allows for lower breathing resistance.



### Protective Grill

Flexible cover to protect and retain the shape of the mask and protect the wearer against possible damage to the filter.

## RANGE



## DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-olympus-800-series-832.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 15 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

