TECHNICAL SPECIFICATION



500 Series Moulded Masks

Disposable Moulded Mask FFP3 Valved (532) Box 5 / BEK130-002-M00



DESCRIPTION

Disposable mask with 360° comfort foam and exhalation valve for low breathing resistance. The adjustable 4-point head strap means it can be fitted comfortably to all head sizes and shapes.

OPTIONS

Disposable Moulded Mask FFP3 Valved (532) Box 5 (BEK130-002-M00)

SAFETY STANDARDS

EN 149















SPECIFICATIONS

Classification

FFP3 (Filtering Facepiece Particulate)

Usage

NR (Non-Reusable)



Activated Carbon Layer

No

Maximum Total Inward Leakage (TIL)

2%

UK Assigned Protection Factor

20



Exhalation Valve

Yes



Nose Bridge

Moulded

Metal Free

Yes

Filter Shelf Life

5 Years



Filter Type

P (Protects Against Solid and Liquid Aerosols)



(D) Resistance to dust clogging

Yes - D marking = passes optional clogging test

Minimum Filtration Efficiency 99% For FFP3 Rated

Nominal Protection Factor

50

Mask Design Moulded



4 Point Harness adjustment system

Yes

Latex free

Yes

Mask Material Polypropylene



Product Weight

15g

FEATURES



Exhalation Valve

Low resistance exhalation valve for easy breathing.



4-Point Adjustable Straps

Metal free, 4-point adjustable straps create a firm and adaptable fit.



Foam Padded Nose Bridge

A mouldable nose bridge and 360° foam area around the inside provide comfort and a firmer fit.

RANGE



DOWNLOADS

Image Pack (ZIP)

doc-disposable-dust-masks-500-series-532.pdf (PDF)

doc-disposable-dust-masks-500-series-532.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





