

20m Touw & Grijper

20m Touw & Grijper / FAR0811



BESCHRIJVING

Valbeveiligingssysteem met een 12 mm diameter kernmanteltouwverankeringslijn met een niet-openbare roestvrijstalen touwgrijper uitgerust met energieabsorber. De verankeringslijn heeft één aansluiting, met de andere kant teruggevouwen en 10 cm gestikt.

OPTIES

20m Touw & Grijper (FAR0811)

VEILIGHEIDSNORMEN

EN 353-2



SPECIFICATIES

Valindicator
Nein

Lengte
20m

Materiaal
12mm Kernmanteltouw

Schokdemper
Extern

Touwuiteinden
1 Zijde 1 Connector. Andere kant teruggevouwen en gestikt 10cm

Beschermende touwkoker
Nein

Afstelapparaat
Niet-openbare roestvrijstalen touwgreep



Gewicht product
3240g

Geleverd met
**2 schroefgatverbindingen in gelegeerd staal.
Poortopening 18 mm. Voldoet aan EN362 Klasse B & M**

DOWNLOADS

 [Pakket afbeeldingen \(ZIP\)](#)

 [doc-far0810-far0811-far0812.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 21 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

