

# TECHNICAL SPECIFICATION



## FilterSpec®

FilterSpec® Black/Smoke FFP3V / ASG134-125-800



### DESCRIPTION

Worn together, safety eyewear and respirators can often reduce each other's effectiveness. Eyewear frames can compromise the seal of the respirator, leading to reduced respiratory protection, and can also cause lens misting. FilterSpec® combines both protective devices into an integrated unit for improved fit and better protection.

### OPTIONS

FilterSpec® Black/Clear FFP2V (ASG124-121-100)

FilterSpec® Black/Clear FFP3V (ASG134-121-100)

**FilterSpec® Black/Smoke FFP3V (ASG134-125-800)**

### SAFETY STANDARDS

EN 149 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 27 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

Face Fit Testing Required  
**Yes**



LIGHT TRANSMISSION BREAKDOWN Lens Shade number  
**1.7**



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s  
Maximum protection for glasses  
**F**

Classification  
**FFP3 (Filtering Facepiece Particulate)**

Usage  
**NR (Non-reusable)**

Minimum Filtration Efficiency  
**99% for FFP3 Rated**

Nominal Protection Factor  
**50**

Mask Design  
**Moulded**

Mask Material  
**Polypropylene**

Material  
**HDPE Mask Holder**



BSI Kitemark  
**Yes**



RADIATION PROTECTION BREAKDOWN filtering effect  
Scale Number  
**5**



Manufacturer's Trademark  
**JSP Dagger**



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional  
**T**



Filter Type  
**P (Protects against solid and liquid aerosols)**



Activated Carbon Layer  
**No**

Maximum Total Inward Leakage (TIL)  
**2%**

UK Assigned Protection Factor  
**20**



Exhalation Valve  
**Yes**

Material  
**Polycarbonate Lens**

Filter Shelf Life  
**5 Years**



Product Weight  
**64g**

## FEATURES



### Integration

FilterSpec's unique design overcomes the problem of ill fitting masks, fogged lenses and non-conformity that can often occur when one item of PPE compromises another.



### Efficient Filter

The easily replaced filters are made from three layers for exceptional performance. Available with low resistance exhalation valve to reduce moisture and CO2 build-up.



### Quality Lens

The FilterSpec® Pro goggle features a 5.5 base curve lens. FilterSpec® lenses have a base curve of 6.5. Both offer optimal coverage and feature anti-mist and anti-scratch lens coatings.

## RANGE



## DOWNLOADS

[Image Pack \(ZIP\)](#)

[doc-filterspec-ffp3-mask.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 27 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

