

TECHNICAL SPECIFICATION



FilterSpec®

FilterSpec® Black/Smoke FFP3V / ASG134-125-800



DESCRIPTION

Worn together, safety eyewear and respirators can often reduce each other's effectiveness. Eyewear frames can compromise the seal of the respirator, leading to reduced respiratory protection, and can also cause lens misting. FilterSpec® combines both protective devices into an integrated unit for improved fit and better protection.

OPTIONS

FilterSpec® Black/Clear FFP2V (ASG124-121-100)

FilterSpec® Black/Clear FFP3V (ASG134-121-100)

FilterSpec® Black/Smoke FFP3V (ASG134-125-800)

SAFETY STANDARDS

EN 149 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 14 Sep 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect
Scale Number
5



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.7



Manufacturer's Trademark
JSP Dagger



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °
Maximum protection for glasses
F



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional
T

Classification
FFP3 (Filtering Facepiece Particulate)



Filter Type
P (Protects against solid and liquid aerosols)

Usage
NR (Non-reusable)



Activated Carbon Layer
No

Minimum Filtration Efficiency
99% for FFP3 Rated

Maximum Total Inward Leakage (TIL)
2%

Nominal Protection Factor
50

UK Assigned Protection Factor
20

Mask Design
Moulded



Exhalation Valve
Yes

Mask Material
Polypropylene

Material
Polycarbonate Lens

Material
HDPE Mask Holder

Filter Shelf Life
5 Years



BSI Kitemark
Yes



Product Weight
64g

FEATURES




Integration

FilterSpec's unique design overcomes the problem of ill fitting masks, fogged lenses and non-conformity that can often occur when one item of PPE compromises another.



Quality Lens

The FilterSpec® Pro goggle features a 5.5 base curve lens. FilterSpec® lenses have a base curve of 6.5. Both offer optimal coverage and feature anti-mist and anti-scratch lens coatings.



Efficient Filter

The easily replaced filters are made from three layers for exceptional performance. Available with low resistance exhalation valve to reduce moisture and CO2 build-up.

RANGE



DOWNLOADS

- [Image Pack \(ZIP\)](#)
- [doc-filterspec-ffp3-mask.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 14 Sep 2025 / Copyright 2018 - 2025, JSP Limited. All Rights Reserved.

